

## Pneumatic 4" Extended Cut-Off Tool



COTE-04



### ► FEATURES

- Built-In Spindle Lock
- Rear Exhaust
- Built-In Cushion Grip
- Push to Adjust Safety Guard
- 11 Position Adjustable Swivel Guard (126° Adjustable Range)
- Powerful Motor (1.0 HP/0.7KW)

PART NO.	SIZE	TYPE	MAXIMUM RPM	AIR INLET	AIR CONSUMPTION	LENGTH	WEIGHT	NOISE LEVEL	RECOMMENDED AIR PRESSURE	ARBOR
COTE-04	4"	Pneumatic	14,000	1/4" NPT	4 CFM (113 L/min)	14-3/4" (377mm)	3.7 lbs (1.7kg)	85 dB(A)	90 PSI (6.2 Bar)	3/8" (10mm)



## ULTRACUT ABM Series

- Has Bi-Directional Rotation
- Made with The Highest Quality Diamond Grits
- Cuts Angle Iron, Pipe, Electrical Conduit, Re-Bar, Metal Stud, Structural Metal, Sheet Metal, Grid, and Stainless Steel, Wood, Plastics, Composite Materials, Masonry and Concrete



PART NO.	SIZE	THICKNESS	MAXIMUM RPM	ARBOR
ABM0338	3"	1.5mm	20,000	3/8" (10mm)
ABM0438	4"	1.5mm	15,000	3/8" (10mm)

## Pneumatic 3" Reversible Cut-Off Tool



COTR-03



### ► FEATURES

- Special Hub Allows for Left or Right Turning Cutting Action
- Collar Operated Easy Directional Change
- Safety Throttle Lever
- Rear Exhaust
- Powerful Motor (0.85HP/0.63 KW)

PART NO.	SIZE	TYPE	MAXIMUM RPM	AIR INLET	AIR CONSUMPTION	LENGTH	WEIGHT	NOISE LEVEL	RECOMMENDED AIR PRESSURE	ARBOR
COTR-03	3"	Pneumatic	20,000	1/4" NPT	4 CFM (113 L/min)	8-1/16" (204mm)	2 lbs (0.9 kg)	83 dB(A)	90 PSI (6.2 Bar)	3/8" (10mm)