ATTENTION

PSC-600 REQUIRES GRINDING WHEEL WITH 7/8" (22MM) ARBOR

7/8″(22mm)

7/8" (22mm)

Remove Inner Flange for Cutting*

ALPHA® PNEUMATIC STONE CUTTER

Thank you for purchasing an Alpha® Pneumatic Stone Cutter.

This tool is a workhorse for a complete cutting system. A wide range of accessories allow you to perform many different tasks.

Default Setup: the Inner Flange for Cutting is installed on the spindle.*

To use as a Grinder, please remove the Cutting Flange and replace with additional Flange for Grinding which can be found in the accesories bag.

*Factory Installed

Inner Flange for Grinding

TRY OUR NEW GRINDING PRODUCTS DESIGNED FOR NATURAL/ENGINEERED STONE, SINTERED SLABS AND PORCELAIN PANELS



SPIKE DISC

- Excellent for Removing Glass Fiber Reinforcement
- Unique Open-Mesh Layout Reduces Clogging and Heat Build-Up
- Optimized Diamond Grits Provide A Consistent Performance
- Sandwiched-Rubber Cushioned Light-Weight Body Reduces Noise & Vibration
- Each Diamond Bead Has Multiple Diamond Grits To Maintain A Sharp Cutting Capability for A Long Time



PART NO	SIZE	ARBOR(S)	GRIT
VCS4535	4-1/2"	7/8" (22mm)	35
VCS4550	4-1/2"	7/8" (22mm)	50
Maximum RPM 13,200			

PART NO	SIZE	ARBOR(S)	GRIT
VCS5035	5"	7/8" (22mm)	35
VCS5050	5"	7/8" (22mm)	50
Maximum RPM 12,200			



103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114 www.alpha-tools.com

FL2272-2/20

(F1)(D)(in)(Y)(D)(G+)



VEXCEL GRINDING DISC

- Designed for Heavy-Duty Material Removal Applications
- Great for Granite, Engineered Stone, Quartzite, Marble, Concrete and Sintered Slabs
- Diamond Mesh Sizes Available #25 (Extra Course), #35 (Course), #50 (Medium), #80 (Fine)
- Robust Diamond Grits for Maximum Performance
- Fluoric Rubber Backing To Reduce Noise and Vibration

PART NO	SIZE	ARBOR(S)	GRIT
VDR4525	4-1/2"	7/8" (22mm)	25
VDR4535	4-1/2"	7/8" (22mm)	35
VDR4550	4-1/2"	7/8" (22mm)	50
VDR4580	4-1/2"	7/8" (22mm)	80
Maximum RPM 13,200			

PART NO	SIZE	ARBOR(S)	GRIT
VDR5025	5"	7/8" (22mm)	25
VDR5035	5"	7/8" (22mm)	35
VDR5050	5"	7/8" (22mm)	50
VDR5080	5"	7/8" (22mm)	80
Maximum RPM 12,200			





VFLEX SANDING DISC

- Perfect for Sink Rim Shaping and Sanding
- Super Light Tool Eliminates Chipping
 on Delicate Materials
- Flexible Sandwich Construction Reduces Noise and Vibration
- Ideal for Shaping Natural/Engineered Stone and Glass

PART NO	SIZE	ARBOR(S)	GRIT
VDF5035	5"	7/8" (22mm)	35
VDF5050	5"	7/8" (22mm)	50
VDF5080	5"	7/8" (22mm)	80
Maximum RPM 5,000			

Alpha Professional Tools[®]

103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114 www.alpha-tools.com