



PWC-658

6" PNEUMATIC HIGH-SPEED CUTTER / GRINDER

The Ultimate Work Horse for **Stone Fabricators**



Center Water-Feed System

Toolbox Air/Water Twin Hose Assembly (30ft / 9.1m)

Avoid Accidental Start

Spring Return Throttle to

SPECIFICATIONS

Model	PWC-658 / PWC-514
	90 PSI (6.2 Bar)
Air Consumption	33 CFM (934L/min)
	4.6 lbs (2.1 kgs)
No Load Speed	10,000 RPM / 12,000 RPM
Air Inlet	3/8" NPSM
Water Inlet	1/8" BSPT
Spindle	5/8"-11 / M14-2
Max. HP	1.4 HP
Max. Disc Size	6" (150mm) / 5" (125mm)

EQUIPMENT INCLUDED

Air/Water Twin Hose Assembly (30ft / 9.1m) Alpha® Elite Q Blade Quad W Adapter Assembly Safety Guard Rust Inhibitor Oil (3.4oz / 100ml) Quick Connect Ball Valve Handle Bracket Assembly Side Handle Hex Wrench (2mm) Hex Wrench (5mm) Spanner Wrench (19mm) Extension Rod and Nylon Lock Nut (M12) Reusable, Stackable Toolbox

PART NO.	MAXIMUM RPM	THREADS	DESCRIPTION
PWC-658	10,000	5/8″-11	6" Pneumatic High-Speed Cutter/Grinder
PWC-514	12,000	M14-2	5" Pneumatic High-Speed Cutter/Grinder

Ouick Connect

Ball Valve

Alpha Professional Tools®

Side Handle

Elite Q

Blade

PHIELITEQ

Rust

Inhibitor

Oil