FOR CHEMICAL EMERGENCY SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT CALL (CHEMTREC) 800-424-9300. THIS MSDS COMPLIES WITH 29 CFR 1919.1200 (THE HAZARD COMMUNICATION STANDARD)

Date of Preparation: May 28, 1996

Material Safety Data Sheet

Section 1 - Chemical Product and Company Identification

Product / Chemical Name:

Diamond Blades (Metal Bonded & Electroplated)

and Grinding Wheels

Distributor Name: Alpha Professional Tools® **Address:** 103 Bauer Drive, Oakland, NJ 07436

Emergency Tel. No.: 800-648-7229

Product Type: N/A Formula: N/A

Section 2 - Hazardous Ingredients

Chemical Name & Common Names		Exposure Limits in Air						*	
		CAS Numbers		ACGIH TLV MG / M³		OSHA PEL MG / M³		Carcinogen (Y / N)	
Cobalt		7440-48-4		. 0.1		0.1		N	
Copper		7440-50-8		. 1.0		1.0		N	
Tin		7440-31-5		NAIF		NAIF		N	
Nickel		7440-02-0		1.0		1.0		Υ	
Iron		7439-86-6		15.0		NAIF		N	
Tungsten Carbide		7440-37-7		. 5.0		5.0		N	
Silicon		7440-21-3		10.0		15.0		N	
Carbon		7440-44-0		3.5		3.5		N	
Chromium		7440-47-3		0.5		1.0		Υ	
Epoxy Resin (hardened)		NAIF		NAIF		NAIF		N	

(*) Materials are regulated by OSHA 29 CFR 1910.1200, Hazard Communication Standard.

Section 3 - Physical and Chemical Properties

Vapor Density (AIR=1): N/A Specific Gravity: 7 - 14 Solubility in Water: Insoluble

Vapor Pressure, mmHg at 20°C: N/A

Appearance and Odor: Solid metallic appearance, Odorless. (Resin portion may give off odor in use)

Percent Colatile by Vol: 0

Solubility in other Solvent: Soluble in strong mineral

acids

Melting Point or Range: 630°C - 1200°C

Boiling Point or Range: N/A

Evaporation Rate (Butyl Acetate=1): N/A

Solubility in Alcohol: Insoluble Melting Point of Resin: N/A Specific Gravity of Resin: 0.7 - 1.2

*Diamond Electroplated Blades have Ni-plated diamond grains on steel center.

Section 4 - Fire and Explosion

Flash Point, °F: N/A

Auto Ignition Temperature, °F: N/A

Flammable Limits in Air, Vol%: N/A

Fire Extinguishing Materials: N/A Special Fire Fighting Procedures: N/A Unusual Fire & Explosion Hazards: N/A

Section 5 - Health Hazard Information

Symptoms of Overexposure for each Potential Route of Exposure.

Inhaled: During sawing or grinding, dust can irritate nose or throat, which may cause coughing, wheezing or shortness of breath.

Contact with skin or eyes: During sawing or grinding, some may experience skin or eye irritation from dust.

Contact through skin: During sawing or grinding, some may experience skin irritation from dust.

Health effects or risks from exposure: Acute: (During sawing or grinding) coughing, wheezing or shortness of breath. Chronic: (During sawing or grinding) may affect to breathing capacity.

First Aid (Emergency Procedures)

Eye contact: If irritation occurs, flush with copious amount of water. If irritation persists, seek medical attention. **Skin Contact:** If irritation or rash occurs, wash affected area thoroughly with soap and water. Seek medical attention. **Inhaled:** If symptoms develop (coughing, wheezing, shortness of breath, etc.) remove from the exposure and seek medical attention.

Suspected cancer agent?: Yes: This product's ingredients are listed and regulated as carcinogen by OSHA 29 CFR 1919.1200, Hazard Communication Standard.

Medical conditions aggravated by exposure: NAI

Incompatibility (Materials to avoid): NAIF

Section 6 - Corrosivity and Reactivity Data

Stabiltiy: Stable Hazardous decomposition products (Including

combustion products): NAIF

Hazardous polymerization: Will not occur

Section 7 - Spill, Leak, and Disposal Procedures

Spill or leak response procedures (Including employee protection measures): Solid metal, N/A

Preparing wastes for disposal (Container type, neutralization, etc.): Standard methods consistent with applicable federal, state and local regulations.

Section 8 - Special Handling Information

Ventilation and Engineering Controls: During sawing or grinding, handle with adequate ventilation for nuisance dust. See OSHA 29 CFR 1910.94 (Ventilation) and CFR 1910.1000 (Air contaminants). See ANSI standard B7-1, Section 2.

Respiratory Protection: During sawing or grinding, use an appropriate NIOSH approved respirator if airborne dust concentrations exceed the appropriate PEL or TLV.

Eye Protection: Recommended (during sawing or grinding)

Gloves: Recommended (during sawing or grinding)

Other Clothing and Equipment: During sawing or grinding, use other protective equipment such as flame retardent clothing if applicable, See OSHA 29 CFR 1910.215 (Hearing Protection).

Work Practices and Hygienic Practices: During sawing or grinding, use safety guards. Make sure all the guards are in place.

Other Handling and Storage Equipments: See ANSI standard B7.1.

Protective Measures During Maintenance of Contaminated Equipment: NAIF

Note: N/A = Not Applicable NAIF = No Applicable Information Found