

# NEW

# AIR-830

# ALPHA®

## HIGH-PERFORMANCE PNEUMATIC POLISHER



**4,000 RPM Gear Set**  
for Best  
Quality Results

**Silicon Gear Head  
Cover Provides  
Cushion and  
Keeps Hands  
Warm**

**New Splash Guard**  
Visibility Without  
Being Splashed

**Newly Developed  
Motor Produces  
More Power**

### Ergonomic and lightweight for better maneuverability



**Enhanced  
Spindle Shaft  
for Easy  
Tool Removal**  
(Wrench Included)

#### SPECIFICATIONS

Model.....	AIR-830/834
Air Pressure.....	85 PSI (6 Bar)
Air Consumption.....	15 CFM (425L/min)
Weight.....	2.75 lbs (1.2 kgs)
No Load Speed.....	4,000 RPM
Air Inlet.....	1/4" BSPP
Water Inlet.....	1/8" BSPP
Spindle.....	5/8"-11 / M14-2

#### EQUIPMENT INCLUDED

- Air Hose (15ft / 4.5m)
- Water Hose (15ft / 4.5m)
- Side Handle (reversible)
- Rust Inhibitor Oil (6.7oz / 200ml)
- Screw (w/ O-Ring Seal for Oil Port)
- Exhaust Hose with Clamp
- Spring Washer
- Splash Guard
- Double End Wrench (19mm / 22mm)
- Phillips Screwdriver
- Water Quick Coupler w/ Shut Off Valve
- O-Ring (O-Ring for Water Valve Repair)

**Optional C-Handle**



**Water Quick Coupler  
w/ Shut Off Valve**



**15ft. All-Weather Hoses  
with Flexibility Down To  
-40°F Or +140°F  
(-40°C To +60°C)**



Part No  
1030-0004



### Alpha Professional Tools®

103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114

www.alpha-tools.com

Copyright © 2019 Alpha Professional Tools. All rights reserved.



FL2268-09/19

# NEW

# ALPHA®

# AIR-850

## HIGH-PERFORMANCE PNEUMATIC POLISHER

**5,500 RPM Gear Set**  
for Best Productivity

**Ergonomic and lightweight**  
for better maneuverability

**Silicon Gear Head Cover Provides Cushion and Keeps Hands Warm**



**Enhanced Spindle Shaft for Easy Tool Removal**  
(Wrench Included)

**New Splash Guard**  
Visibility Without Being Splashed

**Newly Developed Motor Produces More Power**

### SPECIFICATIONS

Model.....	AIR-850/854
Air Pressure.....	85 PSI (6 Bar)
Air Consumption.....	15 CFM (425L/min)
Weight.....	2.75 lbs (1.2 kgs)
No Load Speed.....	5,500 RPM
Air Inlet.....	1/4" BSPP
Water Inlet.....	1/8" BSPP
Spindle.....	5/8"-11 / M14-2

### EQUIPMENT INCLUDED

Air Hose (15ft / 4.5m)
Water Hose (15ft / 4.5m)
Side Handle (reversible)
Rust Inhibitor Oil (6.7oz / 200ml)
Screw (w/ O-Ring Seal for Oil Port)
Exhaust Hose with Clamp
Spring Washer
Splash Guard
Double End Wrench (19mm / 22mm)
Phillips Screwdriver
Water Quick Coupler w/ Shut Off Valve
O-Ring (O-Ring for Water Valve Repair)

**Water Quick Coupler w/ Shut-Off Valve**



**15ft. All-Weather Hoses with Flexibility Down To -40°F Or +140°F (-40°C To +60°C)**



**Optional C-Handle**



Part No  
1030-0004



**Alpha Professional Tools®**



103 Bauer Drive, Oakland, NJ 07436 • 800-648-7229 • Fax: 800-286-0114  
www.alpha-tools.com

Copyright © 2019 Alpha Professional Tools. All rights reserved.

FL2258-09/19